



ACCURATE & STABLE

PLACID MEASUREMENT MICROPHONES

Discover a wide selection of our measurement microphones according to your sound measurement needs

PMP
40

Placid Instruments BV

Newtonlaan 115

Office No. 2.21

3584 BH UTRECHT

THE NETHERLANDS

info@placidinstruments.com

www.placidinstruments.com

ASK US!
HERE





PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com

PLACID PMP40

7 mm Pre-Polarized Free-field Microphone, Class 2



Specification

Frequency Range

20 Hz to 20 kHz

Dynamic Range

30 to 126 dB(A)

Nominal Sensitivity

50 mV/Pa

The PMP40 is a 7mm pre-polarized free-field microphone, classified per IEC 61094 as WS3F type 2.



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com

Specification

Basics

The PLACID PMP40 is a high-precision condenser microphone manufactured in compliance with the IEC 61094-4 requirements and classified as a class 2 microphone. The PMP40 microphone is optimized for free-field measurements. As all PLACID microphones, the PMP40 comes with an individually calibration certificate.

Connectivity

The PLACID PMP40 microphone requires a standardized 7 mm BNC preamplifier that does not need to provide polarization.

Uses

The PMP40 is a robust and stable microphone and is being used as an all-round free field microphone suitable for laboratory as well as field jobs.

Daily usage

PLACID recommends calibration before and after each measurement with a calibrator.

Individual calibration

All PLACID microphones are being calibrated in a controlled laboratory environment using traceable calibration equipment complying with ISO17025 standards.

We recommend that all PLACID microphones are re-calibrated every year to guarantee an optimized usage.

PLACID Traceable Calibration is performed by our qualified staff and under controlled conditions according to the procedures and standards such as ISO17025.

Quality

All PLACID microphones are made of high-quality materials that will ensure long stability and durability.

The microphone diaphragm, body, and protection grid are made of high-grade stainless steel, which makes the microphone resistant to physical damage. PLACID offers 2 years warranty against defective materials and workmanship.



PLACID INSTRUMENTS BV

Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS

Phone Landline: +31 302106021

Worldwide (except Europe): +31 613915102

Europe: +31 622813335

info@placidinstruments.com

www.placidinstruments.com

Datasheet PLACID PMP40 Microphone



Class / type	2
Polarization	0 V
Frequency range	20 Hz to 20 kHz
Dynamic range	30 – 126 dB(A)
Nominal Sensitivity	50 mV/Pa
Temperature range, operation	-30 – 75 Celsius
IEC 61094 Designation	WS3F Type 2
Humidity operating Range	0 to 90 % RH
Ventilation	Rear
Weight	9.2 grams
Height	65 mm
Diameter	7 mm