



PLACID ACCELEROMETERS

Specification

Models / Unit	Type	Sensitivity (mV/g)	Measurement Range (g)	Transverse Sensitivity	Frequency Range (Hz)	Temperature Range (C)	Excitation Voltage (V)	Housing Material	Cable Type
PQV1050	Single	100	+/- 50	≤5%	0.5 - 12000	-40 to +120	+12 - +24 (IEPE)	Stainless Steel	TNC
PQV1050-4		40	+/- 50	≤5%	0.5 - 12000	-40 to +120		Stainless Steel	TNC
PQV1500S		10	+/- 500	≤5%	0.5 - 10000	-40 to +120	+12 - +30 (IEPE)	Stainless Steel	M5
PQV1500T		10	+/- 500	≤5%	0.5 - 10000	-40 to +120		Stainless Steel	M5
PQV3010	Triaxial	500	+/- 10	≤5%	0.5 - 5000	-40 to +125	+12 - +24 (IEPE)	Stainless Steel	M5
PQV3050		100	+/- 50	≤5%	0.5 - 7000	-40 to +125		Stainless Steel	M5
PQV3500		100	+/- 500	≤5%	0.5 - 10000	-10 to +55	+18 - +30 (IEPE)	Aviation Aluminum	M12

PLACID is able to customize different products, will quote and provide delivery date according to customer demand



Placid Instruments BV
Newtonlaan 115
Office No. 2.21
3584 BH UTRECHT
THE NETHERLANDS
info@placidinstruments.com

**ACCURATE,
EASY TO USE**

www.placidinstruments.com